

U.S. Application No.: 10/808,969  
AMENDMENT A

Attorney Docket: 4052.001

**IN THE CLAIMS:**

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Claims 1-19. (Cancelled)

20. (currently amended) The warming/chilling apparatus according to claim 19, wherein the high temperature is at least 50°C and the low temperature is at most +10°C.

21. (previously presented) The warming/chilling apparatus according to claim 20 wherein the low temperature is less than 0°C.

22. (currently amended) The warming/chilling apparatus according to claim 25 [[19]], wherein the heating device and the cooling device are designed and arranged relative to each other in such a way that a change between the high and the low temperatures is possible within a minute.

23. (previously presented) The warming/chilling apparatus according to claim 22, wherein the heating device and the cooling device are designed and arranged relative to each other in such a way that a change between the high and the low temperatures is possible within 30 seconds.

24. (currently amended) The warming/chilling apparatus according to claim 25 [[19]], wherein the heating/cooling element has a heating/cooling face, and the heating/cooling face includes at least one surface of the heating device or surface of the cooling device.

{WP318853:1}

U.S. Application No.: 10/808,969  
AMENDMENT A

Attorney Docket: 4052.001

25. (currently amended) A ~~The warming/chilling apparatus according to claim 24,~~  
comprising:

a heating/cooling element, and  
a heating device and a cooling device for alternately heating and cooling the  
heating/cooling element to a high and a low temperature respectively,

wherein the heating device and the cooling device are designed and arranged relative to  
each other in such a way that the change between the high and the low temperature is possible  
within three minutes,

wherein the temperature difference between the high and the low temperatures is at least  
40°C,

wherein the heating/cooling element has a heating/cooling face, and the heating/cooling  
face includes at least one surface of the heating device or surface of the cooling device, and

wherein a surface of the heating device forms the heating/cooling face, the cooling device  
is attached arranged on the side of the heating device, that is remote from the heating/cooling  
face, and the heating device has a low heat capacity.

26. (previously presented) The warming/chilling apparatus according to claim 25, wherein  
the heating device is an electrical heating plate.

27. (previously presented) The warming/chilling apparatus according to claim 26, wherein  
the thickness of the heating plate is less than 0.5 mm.

28. (currently amended) The warming/chilling apparatus according to claim 25 [[19]],  
wherein the cooling device is a thermoelectric element.

{WP318853;1}

U.S. Application No.: 10/808,969  
AMENDMENT A

Attorney Docket: 4052.001

29. (currently amended) The warming/chilling apparatus according to claim 28 [[19]], wherein a cooling body for dissipating excess heat is arranged at the side of the thermoelectric element that is remote from the heating device.

30. (currently amended) A ~~The warming/chilling apparatus according to claim 24,~~  
comprising:

a heating/cooling element, and

a heating device and a cooling device for alternately heating and cooling the heating/cooling element to a high and a low temperature respectively,

wherein the heating device and the cooling device are designed and arranged relative to each other in such a way that the change between the high and the low temperature is possible within three minutes,

wherein the temperature difference between the high and the low temperatures is at least 40°C,

wherein the heating/cooling element has a heating/cooling face, and the heating/cooling face includes at least one surface of the heating device or surface of the cooling device, and

wherein the heating device and the cooling device are so designed that a surface of the heating device and a surface of the cooling device alternately form the heating/cooling face.

31. (previously presented) The warming/chilling apparatus according to claim 30, wherein the heating device includes tube-like portions for the flow of a heating fluid and the cooling device includes tube-like cooling portions for the flow of a cooling fluid, which are each made from an elastic material, and that there is at least one pressure producing means for alternately producing high and low fluid pressure in the heating fluid and the cooling fluid respectively, and wherein the change of high and low fluid pressure is effected in such a way that the heating fluid is at a high fluid pressure while the cooling fluid is at a low fluid pressure and vice-versa, and wherein the tube-like heating portions and the tube-like cooling portions as well as the high fluid

(WP318853:1)

- 4 -

U.S. Application No.: 10/808,969  
AMENDMENT A

Attorney Docket: 4052.001

pressure and the low fluid pressure are matched to each other in such a way that those tube-like portions in which the high fluid pressure prevails cover over the tube-like portions in which the low fluid pressure prevails.

32. (previously presented) The warming/chilling apparatus according to claim 31, wherein in that the tube-like portions are arranged in mutually juxtaposed relationship on a common plate.

33. (previously presented) The warming/chilling apparatus according to claim 31, wherein the tube-like portions comprise a rubber-metal mixture.

34. (canceled)

35. (previously presented) A pain treatment unit comprising a heating device and a cooling device for alternately heating and cooling a heating/cooling element to a high and a low temperature respectively, wherein

the heating/cooling element comprises an electrical heating plate having a low heat capacity and a thickness less than 0.5 mm as the heating device, a surface of which forms a heating/cooling face of the heating/cooling element;

the heating/cooling element comprises a thermoelectric element as the cooling device which is fixed by means of a thermally conductive adhesive to the side of the heating device, that is remote from the heating/cooling face; and

the electrical heating plate and the thermoelectric element are driven such that a change between the high and the low temperature takes place within three minutes and that the temperature difference between the high and the low temperatures is at least 40°C.

36. (canceled)

{WP318853:1}